



Weighing Technology

A Higher Level of Precision...A Higher Level of Performance

FS/FS2
SERIES

Stainless Steel Washdown Bench & Platform Scale

- Large 2 Inch Backlit Display
- FS2 with Hermetically Sealed Load Cell and All Stainless Base



Manufactured by an ISO 9001 certified company.



| Model | FS-60 / FS2-60K | FS-150 / FS2-150K | FS-300 / FS2-300K |
|------------------------------|---|--------------------------|-------------------------|
| Capacity | 60 kg / 132 lb | 150 kg / 330 lb | 300 kg / 660 lb |
| Readability | 0.01 kg / 0.02 lb / 0.5 oz | 0.02 kg / 0.05 lb / 1 oz | 0.05 kg / 0.1 lb / 2 oz |
| Divisions | 6,000 | 7,500 | 6,000 |
| Weighing Units / Functions | kg, lb, lb : oz | | |
| Stabalization Time (seconds) | < 1.5 | | |
| Tare Range | To capacity by subtraction | | |
| Power Source | Built-in rechargeable battery or external power adapter (included) | | |
| Construction | Stainless steel platform, pillar, indicator and housing (Aluminum load receiving structure on FS models / All stainless steel base and hermetically sealed load cell on FS2 models) | | |
| Display | 2 inch / 51 mm wide viewing angle backlit LCD | | |
| Pan Size (W x D x H) | 16.7 x 20.7 x 4.5 inches / 425 x 525 x 120 mm | | |
| Dimensions (W x D x H) | 16.7 x 20.7 x 36.8 inches / 425 x 525 x 935 mm | | |
| Operating Environment | 32° ~ 104° F non condensing R.H. ≤ 85% | | |
| Net Weight | 48.4 lb / 22 kg | | |
| Shipping Weight | 50 lb / 22.3 kg | | |
| NEMA/IP Rating | FS Series - NEMA 4X / IP 65 / FS2 Series - NEMA 4X / IP 68 | | |
| Options | Stainless steel wheel kit | | |

FS / FS2 Series



Features

- All stainless steel housing and pan
- Heavy duty construction
- Sealed electronics. Waterproof tactile keypad
- Low profile
- Large LCD display with wide angle viewing and backlight
- Extendable pillar (another 5.5 inches / 140 mm)
- Reads in kilograms, pounds and pounds : ounces
- Built-in rechargeable battery or external power adaptor
- Accumulation function
- Zero tracking
- Automatic power save
- Low battery indicator
- Auto-calibration function
- Adjustable stainless steel feet with rubber inserts
- Indicator rotates through 135 degrees
- Gravitational correction software (FS2 models only)

Benefits

- Easy to clean for food processing or harsh environments
- Will withstand harsh industrial operation
- Improved water and dust resistance
- Easy to load and unload platform only 4.7 inches / 120 mm high
- Easy to see weight values from a distance, reduces mistakes
- Enables bulky objects to be weighed
- Flexibility of operation
- Portability - battery lasts a minimum of 120 hours (without back light)
- Allows you to add together consecutive weights to arrive at a total
- Assures that you always start weighing at zero
- Conserves battery power
- Alerts you to charge the battery, saving downtime
- Ensures accuracy
- Balance remains level for accurate results on uneven working surfaces - anti-slip
- Enables viewing from all angles
- Enables you to input different G acceleration factors